
AudioRepr

Release 0.0.2

Lei Ma

Dec 30, 2020

CONTENTS

1 Tutorials	3
1.1 Audiorepr Tutorials	3
2 Audiolizer Modules	5
2.1 AudioRepr - audiolize	5
2.2 AudioRepr - data	5
2.3 AudioRepr - mapper	5
2.4 AudioRepr - command	6
3 HISTORY	7
3.1 History	7
4 Indices and tables	9
Python Module Index	11
Index	13

A python package to represent data using musical notes. Similar to visualization packages, `audiorepr` takes in data and audiolize the data.

Here is a demo using a [sample of covid19 data](#) in Europe. The audio is the result of this package while the video is made with GarageBand. (See the tutorials for the code.)

Warning: This documentation is still a WIP.

1.1 Audiorepr Tutorials

1.1.1 Installation

```
pip install audiorepr
```

1.1.2 Command Line

The package comes with a command line tool `audiorepr`.

The command line tool `audiorepr` has several options.

- `-d` or `--data`: file path to a csv file or url of a csv file.
- `-t` or `--target`: audio file to be save as.
- `-c` or `--column`: use a specific column from the dataset. This can be used as many times as one needs to include many columns. If not specified, all columns in the data will be used.

```
audiorepr create -d path_to_data.csv -t test_package.midi -c DE -c FR
```

Or using a csv file from a URL

```
audiorepr create -d https://gist.githubusercontent.com/emptymalei/  
↪90869e811b4aa118a7d28a5944587a64/raw/1534670c8a3859ab3a6ae8e9ead6795248a3e664/ecdc  
↪%2520covid%252019%2520data -t test_package.midi -c DE -c FR
```

1.1.3 Python

The module `audiolize` in `audiorepr` contains a function `audiolizer`. `audiolizer` is the primary function we will need for to generate our audio file.

- The parameter `pitch_columns` specifies which columns are being used to create the audio.

```
import pandas as pd  
from audiorepr import audiolize  
  
ecdc = "https://gist.githubusercontent.com/emptymalei/  
↪90869e811b4aa118a7d28a5944587a64/raw/1534670c8a3859ab3a6ae8e9ead6795248a3e664/ecdc  
↪%2520covid%252019%2520data"
```

(continues on next page)

(continued from previous page)

```
df = pd.read_csv(ecdc)
audiolize.audiolizer(df, target="ecdc-covid19-by-date.midi", pitch_columns=["DE", "AT
↔", "FR"])
```

AUDIOLIZER MODULES

2.1 AudioRepr - audiolize

Documentation for *audiorepr.audiolize*

2.1.1 Audiolize

2.2 AudioRepr - data

Documentation for *audiorepr.data*

2.2.1 Data Transformation and Validation

2.3 AudioRepr - mapper

Documentation for *audiorepr.mapper*

2.3.1 Mapper Class

```
class audiorepr.mapper.BaseMapper (pitch_min=None, pitch_max=None, data_min=None,  
                                     data_max=None, **params)
```

```
    __init__ (pitch_min=None, pitch_max=None, data_min=None, data_max=None, **params)  
        Initialize self. See help(type(self)) for accurate signature.
```

```
    __weakref__  
        list of weak references to the object (if defined)
```

```
class audiorepr.mapper.LinearMinMaxMapper (pitch_min=None, pitch_max=None,  
                                             data_min=None, data_max=None, **params)
```

```
    __init__ (pitch_min=None, pitch_max=None, data_min=None, data_max=None, **params)  
        Initialize self. See help(type(self)) for accurate signature.
```

2.4 AudioRepr - command

Documentation for *audiorepr.command*

3.1 History

This is the CHANGELOG of the package.

3.1.1 [0.0.1] - 2020-12-24

Initialization of the project

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

a

`audiorepr.mapper`, 5

Symbols

`__init__()` (*audiorepr.mapper.BaseMapper* method),
5

`__init__()` (*audiorepr.mapper.LinearMinMaxMapper*
method), 5

`__weakref__` (*audiorepr.mapper.BaseMapper* at-
tribute), 5

A

`audiorepr.mapper`
module, 5

B

`BaseMapper` (*class in audiorepr.mapper*), 5

L

`LinearMinMaxMapper` (*class in audiorepr.mapper*), 5

M

module
`audiorepr.mapper`, 5